

ARLUXE

www.arluxe.us

STONE CORE FLOORING

2026

NEWEST
COLLECTION

BOHO

BOHO
COLLECTION

floor
score

NSF Certified



WATERPROOF



SILENT
FLOOR



UNILIN
CLICK

NEWEST
SPC FLOOR

AUTUMN TIMBER

BOHO COLLECTION



ARLUXE

Trend Interior Design Style
High Quality SPC Flooring

BETTER PERFORMANCE

COLOR TREND

30MIL

WEAR LAYER

8MM

THICKNESS



AUTUMN TIMBER

Plank Size 9"x48"
Packing: 8 Pcs x Box
24 Sq.Ft x Box



NEWEST
SPC FLOOR

AMBERWOOD

BOHO COLLECTION



ARLUXE

Trend Interior Design Style
High Quality SPC Flooring

BETTER PERFORMANCE

COLOR TREND

30MIL

WEAR LAYER

8MM

THICKNESS



AMBERWOOD

Plank Size 9"x48"
Packing: 8 Pcs x Box
24 Sq.Ft x Box



NEWEST
SPC FLOOR

HONEY WALNUT

BOHO COLLECTION



ARLUXE

Trend Interior Design Style
High Quality SPC Flooring

BETTER PERFORMANCE

COLOR TREND

30MIL

WEAR LAYER

8MM

THICKNESS



HONEY WALNUT

Plank Size 9"x48"
Packing: 8 Pcs x Box
24 Sq.Ft x Box



BOHO COLLECTION

BETTER
PERFORMANCE
30MIL
WEAR LAYER

COLOR TREND
8MM
THICKNESS



Plank Size 9"x48"
Packing: 8 Pcs x Box
24 Sq.Ft x Box



BOHO COLLECTION

BETTER
PERFORMANCE
30MIL
WEAR LAYER

COLOR TREND
8MM
THICKNESS

BOHO COLLECTION

PRODUCT TECHNICAL PROPERTIES & SPECIFICATIONS

Product Type	
Items	Dimension
EPC (Light SPC) Flooring	8.0mm X 228mm X 1220mm


Product Specifications			
No	Performance	Standard	Characteristics
1	Plank Size		9" X 48" (228mm X 1220mm)
2	Wear Layer Thickness		30mil (0.75mm)
3	Acoustic Underlay		2.0mm IXPE (High Density)
4	Bevel Edge		Micro Bevel
5	Click Profile		Valinge 2G click joint
6	Acoustic Underlay		Thickness : 1mm High Density IXPE
7	Dimensional Stability - 80°C/6H	ISO 23999	≤ 0.15%
8	Curing after 23°C/6H	ISO 23999	≤ 0.50mm
	Curing after 80°C/6H	ISO 23999	≤ 1.2mm
10	Residual Indentation	ASTM1914	≤ 0.2mm
11	Fire Resistance	EN13501-1	B _s -S1
12	Slip Resistance	DIN51130 EN13893	R10 DS
15	Color Fastness	ISO105-B02	≥ 6
16	Static Electrical Propensity	EN 1815	< 2.0 kV
17	Abrasion Resistance	EN660-2	< 0.015g (Group T)
18	Chemical Resistance	ISO 26987	Pass Class 0
19	Thermal Resistance	ISO8302	0.029 m ² k/W
20	Heat resistance	EN 12524	max 27 degrees
Environment/Certificate		Standard	Characteristics
21	CE Certificate		Conform
22	FLOOR SCORE		Conform
23	GREEN GUARD Certificate		GREEN GUARD GOLD



Plank Size 9"x48"
Packing: 8 Pcs x Box
24 Sq.Ft x Box



NEWEST
SPC FLOOR



ARLUXE

GENERAL CATALOG 2026 – HOME Edition/Edición 2 | Ref: 05463 Edited and designed: / Editado y diseñado: ARLUXE Publishing: Publicado: FEBRUARY 2024 Printed: / Impreso: UNITED STATES LEGAL INFORMATION: / INFORMACIÓN LEGAL: © TILE CONNECTION. Reserves the right to introduce modifications or changes as deemed appropriate. All colors in this catalogue should be considered as approximated. The entire contents of this catalogue are copyright. No pictures, texts, illustrations or graphic concepts may be reproduced, either wholly or partially, without the express permission of TILE CONNECTION© TILE CONNECTION. Se reserva el derecho de hacer variaciones y modificaciones que se consideren oportunas. A causas de los procesos de impresión, los colores que aparecen en este catálogo deben considerarse aproximados, no exactos. La información de este catálogo está protegida en su totalidad por copy right. Está prohibida la reproducción total o parcial de los textos, ilustraciones, imágenes y representaciones gráficas sin la autorización expresa de DECO DESIGN DISTRICT. DECO DESIGN DISTRICT. Miami, FL USA WWW.ARLUX.US 5202 TAMPA WEST BLVD, Tampa, FL 33634